



PRODUCT LIST

Dukkeo duct tape factory, is a professional R & D manufacturing integrated duct tape manufacturer. The factory with 15 years of senior experience in hot melt R & D with 2 senior engineers, can fully guarantee the stability of product quality; and in 2012 to add a new duct double-sided adhesive coating machine.

EMAIL: info@ducttape.cn

WEB: ducttape.top

**ADD: Industrial Park, Sujiatun
District, Shenyang,
Liaoning, in China**



CLOTH / DUCT TAPE



Product	Total Thickness		Initial Tack	Peel Adhesion		Tensile Strength		Elongation% at break
	(um)	(mil)	(#)	(n/in)	ASTM D-3330 (oz/in)	(n/in)	ASTM D-3759 (lb/in)	D-3759
DT-130	130	5.1	5†	10†	36	50†	11	12%
DT-150	150	5.9	8†	12†	43	50†	11	12%
DT-170	170	6.7	10†	15†	54	65†	15	12%
DT-190	190	7.5	10†	15†	54	70†	16	14%
DT-210	210	8.3	12†	16†	57	70†	16	14%
DT-230	230	9	12†	17†	61	80†	18	15%
DT-250	250	9.8	12†	18†	65	95†	21	15%
DT-270	270	10.6	12†	18†	65	95†	21	15%
DT-290	290	11.4	13†	19†	68	95†	21	15%

Specification: General Purpose; Adheres well to relatively smooth surfaces and sticks well when wrapped around itself
 Application: Including industrial, DIY bundling, wrapping and marking

NATURAL RUBBER DUCT TAPE



Product	Total Thickness		Initial Tack	Peel Adhesion		Tensile Strength		Elongation% at break
	(um)	(mil)	(#)	(n/in)	ASTM D-3330 (oz/in)	(n/in)	ASTM D-3759 (lb/in)	D-3759
NRDT-230	230	9	15†	10†	36	70†	16	15%
NRDT-250	250	9.8	18†	12†	43	95†	21	15%
NRDT-270	270	10.6	20†	12†	43	95†	21	15%
NRDT-300	300	11.8	23†	14†	50	95†	21	15%
NRDT-360	360	14.1	25†	15†	54	95†	21	15%
NRDT-420	420	16.5	25†	15†	54	95†	21	15%

Features: It is made of gauze and coated with natural rubber; it has balanced, Peeling force, initial adhesion, tensile strength; waterproof and leakproof, Anti-corrosion and easy to tear, it is a high-adhesive tape.
 Sealing and splicing of pipes; widely used in office, packaging, transportation, Transportation, construction and other industries.



HOT MELT CLOTH DUCT TAPE



Product	Total Thickness		Initial Tack	Peel Adhesion		Tensile Strength		Elongation% at break
	(um)	(mil)	(#)	(n/in)	ASTM D-3330 (oz/in)	(n/in)	ASTM D-3759 (lb/in)	D-3759
HMDT-230	240	9.4	12†	18†	65	95†	21	15%
NRDT-260	260	10.2	12†	18†	65	95†	21	15%
NRDT-280	280	11	13†	18†	65	95†	21	15%

Application: Better grade duct tape used by Audio Visual companies, Hotel and Banquet facilities to secure electrical cord and cable. Match most carpet colors or can be used in HVAC industry, sealing hatch covers and cargo doors, asbestos abatement, waterproof packaging, floral industry and color coding.

NATURAL RUBBER DUCT TAPE



Product	Total Thickness		Initial Tack	Peel Adhesion	
	(um)	(mil)	(#)	(n/in)	ASTM D-3330 (oz/in)
DSDT-220	220	8.7	10†	12†	43
DSDT-280	280	11	10†	15†	54
DSDT-380	380	15	12†	17†	61

Features: It is made of gauze and coated with natural rubber; it has balanced, Peeling force, initial adhesion, tensile strength; waterproof and leakproof, Anti-corrosion and easy to tear, it is a high-adhesive tape. Sealing and splicing of pipes; widely used in office, packaging, transportation, Transportation, construction and other industries.

DUKKEO DUCT TAPE Colour

